Tongue-and-Groove Cladding.

Extruded aluminum cladding and soffit system

THE LUXOR SYSTEM



Conceptual exploded view of a 6 in. V-Groove profile. Not to scale.

TECHNICAL SPECIFICATIONS

Material · 6063-T5 extruded aluminum

Recyclability · 100% recyclable aluminum

Weight per area · Approx. 1.5 psf

Finish warranty · 15 years (standard)

20 years (Ultra) · 10-week lead time

Aluminum warranty · 50 years

CATALOGUE PROFILES

Reference	Profile	Width	Catalogue length
Z1158	V-Groove	2½ in.	19 ft.
Z1158P	Perforated V-Groove	2½ in.	9 ft.
Z1157	V-Groove	4 in.	12 or 19 ft.
Z1156	V-Groove	6 in.	19 ft.
Z1156P	Perforated V-Groove	6 in.	19 ft.
Z1159	Square Edge	6 in.	19 ft.

APPLICATIONS AND FINISHES

Exterior cladding and soffits. Profiles can be installed horizontally or vertically. Select a sublimated woodgrain finish or solid colour from the catalogue.

FASTENING AND TRIMS

The system uses ZCLIP clips with compatible profiles. Trims complete starters, corners and transitions. Refer to the Accessories & Preparation sheet.

Confirm dimensions, finishes, supplied items and installation conditions with Luxor before ordering.

info@LuxorArchitectural.com

514 585-6558